

www.opledtw.com

Opto Plus LED Corp.
0.30" SMD Type LED Display
OPS-F3010LR | OPS-F3011LR

● **EDIT HISTORY**

Version A: May. 09, 2018


Preliminary Spec.

Version B: Aug. 22, 2019

1. Modify chip spec.
 2. Modify curve graph.
- Add package spec.

Version C: May. 17, 2024

1. Modify recommended soldering pattern.
2. Modify electrical optical characteristics.



www.opledtw.com

Opto Plus LED Corp. 0.30" SMD Type LED Display OPS-F3010LR | OPS-F3011LR

● FEATURES

- 0.30 inch (7.62 mm) Digit Height.
- SMD type.
- Low current operation.
- RoHS Compliant, Pb Free.

● DESCRIPTION

The device are 0.30 inch (7.62 mm) height five digit 7-segment displays.

The device is Opto Plus LED Corp standard LED Display.

This device utilizes Super Red LED chip which are made from AlGaInP on a Transparent GaAs, substrate.

The device has face and segment option, please refer to **PRODUCT APPEARANCE**.

● DEVICE


PART NO.		DESCRIPTION
	OPS-F3010LR-GW	Common Anode Gray face White segment
	OPS-F3011LR-GW	Common Cathode Gray face White segment
	OPS-F3010LR-BW	Common Anode Black face White segment
	OPS-F3011LR-BW	Common Cathode Black face White segment

RoHS Compliance



Pb Free.







www.opledtw.com

Opto Plus LED Corp. 0.30" SMD Type LED Display OPS-F3010LR | OPS-F3011LR

MECHANICAL DIMENSIONS



NOTES: All dimensions are in millimeters. Tolerances are ± 0.25 mm unless otherwise noted.





www.opledtw.com



Opto Plus LED Corp. 0.30" SMD Type LED Display OPS-F3010LR | OPS-F3011LR

● TYPICAL INTERNAL EQUIVALENT CIRCUIT


Turn On Color



DIG.1-DIG.5



OPS-F3010LR (Common Anode)



OPS-F3011LR (Common Cathode)

※EMITTED COLOR : SUPER RED




www.opledtw.com

Opto Plus LED Corp. 0.30" SMD Type LED Display OPS-F3010LR | OPS-F3011LR

● PRODUCT APPEARANCE

The most common reflector color and segment color are show in below diagram.

-GW	-BW
	
※ REFLECTOR COLOR: Gray ※ SEGMENT COLOR: White	※ REFLECTOR COLOR: Black ※ SEGMENT COLOR: White

Opto Plus can customize reflector and segment colors by customer's request. If you have these request please visit www.opledtw.com or contact sales@opledtw.com for more **Standard Product Customization** information.

Part NO. related to reflector and segment colors show as table below.

PART NO.	DESCRIPTION
OPS-F3010LR-GW	Common Anode Gray face White segment
OPS-F3011LR-GW	Common Cathode Gray face White segment
OPS-F3010LR-BW	Common Anode Black face White segment
OPS-F3011LR-BW	Common Cathode Black face White segment



www.opledtw.com

Opto Plus LED Corp.
0.30" SMD Type LED Display
OPS-F3010LR | OPS-F3011LR


● **LR: SUPER RED (AlGaInP/GaAs)**

ABSOLUTE MAXIMUM RATING AT Ta=25°C

Parameter	Symbol	Maximum Rating	Unit
Power dissipation	P _{AD}	48	mW
Continuous forward current	I _{AF}	20	mA
Peak current (duty cycle 1/10, 1kHz)	I _{PF}	40	mA
Reverse voltage	V _R	5	V
Operating temperature	T _{OPR}	-40 to +105	°C
Storage temperature	T _{STG}	-40 to +105	°C

ELECTRICAL - OPTICAL CHARACTERISTICS AT Ta=25°C

Characteristic	Symbol	Condition	Min.	Type.	Max.	Unit
Forward Voltage, (Per Dice)	V _F	I _F =20mA	-	2.1	2.4	V
Reverse Current, (Per Dice)	I _R	V _R =5V	-	-	10	μA
Peak Wavelength	λ _P	I _F =20mA	-	650	-	nm
Dominant Wavelength	λ _D	I _F =20mA	635	-	648	nm
Luminous Intensity	I _V	I _F =20mA	1	-	8.5	mcd
Spectral Line Half-Bandwidth	Δλ	I _F =20mA	-	20	-	nm



www.opledtw.com

Opto Plus LED Corp.
0.30" SMD Type LED Display
OPS-F3010LR | OPS-F3011LR

● LR: BIN GRADE (Unit : mcd) 20mA


Super Red	I	J	K
	1.0 – 3.5	3.6 – 6.0	6.1 – 8.5

● LR: HUE GRADE (λ_D : nm)

1	2	3
635.0 – 640.0	640.1 – 644.0	644.1 – 648.0

● AVAILABLE BIN / HUE TABLE

I1	J1	K1
I2	J2	K2
I3	J3	K3



www.opledtw.com

Opto Plus LED Corp. 0.30" SMD Type LED Display OPS-F3010LR | OPS-F3011LR

● LR: SUPER RED (AlGaInP/GaAs) CURVE

Typical Electro-optical Characteristic Curves
(25 °C Free Air Temperature Unless Otherwise Specified)




Fig.1 FORWARD CURRENT VS. FORWARD VOLTAGE




Fig.2 RELATIVE INTENSITY VS. FORWARD CURRENT




Fig.3 FORWARD VOLTAGE VS. TEMPERATURE




Fig.4 RELATIVE INTENSITY VS. TEMPERATURE




Fig.5 RELATIVE INTENSITY VS. WAVELENGTH





Fig.6 MAX. ALLOWABLE DC CURRENT VS. AMBIENT TEMPERATURE




www.opledtw.com

Opto Plus LED Corp. 0.30" SMD Type LED Display OPS-F3010LR | OPS-F3011LR

● SMT REFLOW SOLDERING INSTRUCTIONS

SMT Soldering Profile

Pb free reflow soldering Profile




- We recommend the reflow temperature 245°C (+/- 5°C).
The maximum soldering temperature should be limited to 260°C.
- Number of reflow process shall be 2 times or less.

● SOLDERING IRON

Basic spec is ≤4 sec when 260°C. If temperature is higher, time should be shorter (+10°C→1 sec). Power dissipation of Iron should be smaller Than 15W, and temperature should be controllable. Surface temperature Of the device should be under 230°C.

● REWORK


- Customer must finish rework within 3 sec. under 350°C.
- The head of soldering iron cannot touch copper foil.




www.opledtw.com

Opto Plus LED Corp. 0.30" SMD Type LED Display OPS-F3010LR | OPS-F3011LR

● REEL DIMENSIONS



● PACKING & LABEL SPECIFICATIONS



● STORAGE CONDITION

In factory original sealed bag package

TEMPERATURE CONDITION	HUMIDITY CONDITION
5°C ~ 30°C	Below 60%RH

After opened and not in factory original sealed bag package

TEMPERATURE CONDITION	HUMIDITY CONDITION	STORAGE TIME
5°C ~ 30°C	Below 60%RH	Within 4 weeks (MSL as level 2a)