



Opto Plus LED Corp.
0.39" SMD Type LED Display
OPS-D3910SY | OPS-D3911SY

● **EDIT HISTORY**

Version A: Oct. 28, 2020

Preliminary Spec.

Version B: Jun. 14, 2022

1. Modify electrical optical characteristics.
2. Modify curve graph.

Version C: Feb. 11, 2026

Modify electrical optical characteristics.

Confidential Document

● FEATURES

- 0.39 inch (10.0 mm) digit height.
- SMD type.
- Low current operation.
- RoHS Compliant, Pb Free.

● DESCRIPTION

The device are 0.39 inch (10.0 mm) height Dual digit 7-segment display.

The device is Opto Plus LED Corp standard LED Display.

This device utilizes Super Bright Yellow LED chip which are made from AlGaInP

On a transparent GaAs, substrate.

The device has face and segment option, please refer to **PRODUCT APPEARANCE**.

● DEVICE

PART NO.		DESCRIPTION
	OPS-D3910SY-GW	Common Anode Gray face White segment
	OPS-D3911SY-GW	Common Cathode Gray face White segment
	OPS-D3910SY-BW	Common Anode Black face White segment
	OPS-D3911SY-BW	Common Cathode Black face White segment


RoHS Compliance



Pb Free.



● MECHANICAL DIMENSIONS



NOTES: All dimensions are in millimeters. Tolerances are ± 0.25 mm unless otherwise noted.

Opto Plus LED Corp.





0.39" SMD Type LED Display

OPS-D3910SY | OPS-D3911SY


● TYPICAL INTERNAL EQUIVALENT CIRCUIT

Turn On Color

Recommended
Soldering Pattern



OPS-D3910SY (Common Anode)





OPS-D3911SY (Common Cathode)

※EMITTED COLOR : SUPER BRIGHT YELLOW

● PRODUCT APPEARANCE

The most common reflector color and segment color are show in below diagram.

-GW	-BW
	
※ REFLECTOR COLOR: Gray ※ SEGMENT COLOR: White	※ REFLECTOR COLOR: Black ※ SEGMENT COLOR: White

Opto Plus can customize reflector and segment colors by customer's request. If you have these request please visit www.opledtw.com or contact sales@opledtw.com for more **Standard Product Customization** information.

Part NO. related to reflector and segment colors show as table below.

PART NO.	DESCRIPTION
OPS-D3910SY-GW	Common Anode Gray face White segment
OPS-D3911SY-GW	Common Cathode Gray face White segment
OPS-D3910SY-BW	Common Anode Black face White segment
OPS-D3911SY-BW	Common Cathode Black face White segment

Opto Plus LED Corp.

0.39" SMD Type LED Display

OPS-D3910SY | OPS-D3911SY

● SY: SUPER BRIGHT YELLOW (AlGaInP/GaAs)

ABSOLUTE MAXIMUM RATING AT Ta=25°C

Parameter	Symbol	Maximum Rating	Unit
Power dissipation	P _{AD}	48	mW
Continuous forward current	I _{AF}	20	mA
Peak current (duty cycle 1/10, 1kHz)	I _{PF}	40	mA
In-rush current	I _{IR}	40	mA
Supply voltage	V _{DD}	5	V
Reverse voltage	V _R	5	V
Operating temperature	T _{OPR}	-40 to +85	°C
Storage temperature	T _{STG}	-40 to +85	°C

ELECTRICAL - OPTICAL CHARACTERISTICS AT Ta=25°C

Characteristic	Symbol	Condition	Min.	Type.	Max.	Unit
Forward Voltage, (Per Dice)	V _F	I _F =20mA	-	2.1	2.4	V
Reverse Current, (Per Dice)	I _R	V _R =5V	-	-	10	μA
Peak Wavelength	λ _P	I _F =20mA	-	593	-	nm
Dominant Wavelength	λ _D	I _F =20mA	585	-	595	nm
Luminous Intensity	I _V	I _F =20mA	25	-	70	mcd
Spectral Line Half-Bandwidth	Δλ	I _F =20mA	-	20	-	nm

Opto Plus LED Corp.
0.39" SMD Type LED Display
OPS-D3910SY | OPS-D3911SY

● **SY: BIN GRADE (Unit : mcd) 20mA**

Super Bright Yellow	M	N	O
	25.0 - 40.0	40.1 - 55.0	55.1 - 70.0

● **SY: HUE GRADE (λ_D : nm)**

1	2	3
585.0 - 588.0	588.1 - 592.0	592.1 - 595.0

● **AVAILABLE BIN / HUE TABLE**

M1	M2	M3
N1	N2	N3
O1	O2	O3

Opto Plus LED Corp.

0.39" SMD Type LED Display

OPS-D3910SY | OPS-D3911SY

● SY: SUPER BRIGHT YELLOW (AlGaInP/GaAs) CURVE

Typical Electro-optical Characteristic Curves
(25 °C Free Air Temperature Unless Otherwise Specified)




Fig.1—Relative Intensity VS. Wavelength




Fig.2—Relative Luminous Intensity vs. Forward Current




Fig.3—Forward Current vs. Forward Voltage




Fig.4—Relative Intensity(@20mA) vs. Ambient Temperature




Fig.5—Forward Voltage(@20mA) vs. Ambient Temperature




Fig.6—Dominant Wavelength(@20mA)
VS. Ambient Temperature




Fig.7—Max. Allowable DC Current
VS. Ambient Temperature



www.opledtw.com

Opto Plus LED Corp.


0.39" SMD Type LED Display

OPS-D3910SY | OPS-D3911SY

● SMT REFLOW SOLDERING INSTRUCTIONS

SMT Soldering Profile

Pb free reflow soldering Profile



- We recommend the reflow temperature 245°C (+/- 5°C).
The maximum soldering temperature should be limited to 260°C.
- Number of reflow process shall be 2 times or less.

● SOLDERING IRON

Basic spec is ≤ 4 sec when 260°C. If temperature is higher, time should be shorter (+10°C → 1 sec). Power dissipation of Iron should be smaller Than 15W, and temperature should be controllable. Surface temperature Of the device should be under 230°C.

● REWORK


- Customer must finish rework within 3 sec. under 350°C.
- The head of soldering iron cannot touch copper foil.

Opto Plus LED Corp.


0.39" SMD Type LED Display

OPS-D3910SY | OPS-D3911SY

● REEL DIMENSIONS



● PACKING & LABEL SPECIFICATIONS



● STORAGED CONDITION

In factory original sealed bag package

TEMPERATURE CONDITION	HUMIDITY CONDITION
5°C ~ 30°C	Below 60%RH

After opened and not in factory original sealed bag package

TEMPERATURE CONDITION	HUMDITY CONDITION	STORAGE TIME
5°C ~ 30°C	Below 60%RH	Within 4 weeks (MSL as level 2a)